

SPORTS SURFACES

DATA SHEET

SPORMAT SOFT

**Elastic mat consisting of recycled polyurethane foam
and high-quality rubber fibres bound with polyurethane elastomer**

CHARACTERISTICS

Spormat Soft is a mat produced with high quality recycled rubber fibre and polyurethane foam, used as an elastic mat for Pavisint SL 75 – S14 sports surfaces. Spormat Soft floorings ensure outstanding shock absorption properties (over 50% according to DIN V 18032), guaranteeing high standards of comfort and safety.

APPEARANCE

Multi-coloured carpet

CHARACTERISTICS OF THE PRODUCT

Characteristics	U.M.	Value	Tolerance
Specific Weight	Kg/cu.m.	560	±
Width (DIN 7715)	m	1,5	± 1.5%
Thickness	mm	14	± 0.3%
Length	-	approx. 8 m	-
Tensile strength (EN ISO 1798)	mPa·s	0,3 N/sq.mm	-
Elongation at break (EN ISO 1798)	%	min. 50	-

IMPORTANT INSTRUCTIONS

The data shown by the product data sheet refer only to prefabricated Spormat; data will vary according to the type and thickness of the polyurethane resin coating applied.

*The data provided by these data sheets are approximate and the Company reserves the right to modify the same for technical reasons, without prior notice. The solutions proposed do not represent all the possible uses but are merely case studies deriving from Casali's installation experience and are therefore intended only for purposes of illustration. The user is exclusively responsible for the way the products illustrated are used, whether properly or improperly, for evaluating in advance the suitability or otherwise of the product for its requirements and exerting the utmost caution in handling chemical products. **Important: to ensure best colour uniformity of surface laid products, we recommend that you use materials from the same production lot as finishing layer. The Technical Office of Casali's Synthetics Division is at your complete disposal for any further specific information or explanations you may require (phone 071 9162095).***

CASALI
SPORT



Rev. 02/2018